

Features

- ✧ Dual-Side LCD Pole Display
- ✧ With Single-Interval or Dual-Range Division
- ✧ 45 Pre-set Memory keys for saving price
- ✧ P50~P99 50 sets of indirect PLU
- ✧ Give-Change Function
- ✧ Weight Unit: kg/ 100g available
- ✧ Auto Zero Point Tracking
- ✧ Tare Function
- ✧ External Digital-Calibration
- ✧ Gravity-Value setting
- ✧ Anti-cockroach Device
- ✧ Low power & Charging status Indication
- ✧ Stainless Steel Platter
- ✧ Dimension:
Scale: 300 x 330 x 120 mm (WxDxH)
Platter: 300 x 240 mm (WxD)
- ✧ Power Source:
DC: 4Ah/6V Rechargeable battery
(160hr without backlight)
AC: 110V or 220V \pm 10%, 50/60Hz



Option:

1. LED Backlight
2. RS-232 or Relay output Interface

Specifications:

Model	Capacity	Division (single-range)	Division (Dual-range)
AEPL-M-6 AEPL-E-6	6kg	2g	1g/2g
AEPL-M-15 AEPL-E-15	15kg	5g	2g/5g
AEPL-M-30 AEPL-E-30	30kg	10g	5g/10g